

Battery

Battery type	Li-ion battery
Capacity	2.5Ah/63Wh
Rated output voltage	25.2V DC
Max output current	15A
Rated input voltage	36V DC (charging cradle), 5V DC (Micro USB)
Charging current	1A (charging cradle), 0.3A (Micro USB)
Weight	490g (without charging cradle)
Ambient conditions during operation	0°C~+40°C at 10%-85% relative humidity
Storage temperature	0°C~+45°C
Thermal switch and overcurrent protection	✓
LED indicator and buzzer for battery capacity status	✓



Certificate

1. EN 62133 (Battery safety testing) Pending
2. UL 1642 (Lithium cells, standard test) Pending
3. UN 38.3 (transportation of Lithium battery) Pending
4. UL 2054 (household and commercial batteries) Pending
5. EN 60335-1 Pending
6. PSE diamond Pending

Easy detachable battery pack. Charging via standard Micro USB charger or control box. LED indicator and buzzer for battery capacity status. Rechargeable battery that provides mobility to office furniture. Slim and easy mounting dock, perfect for desk applications.

Warning

- Must follow rated input voltage. Do not charge with method other than specified.
- Do not disassemble battery pack.

Battery Capacity

*Operating Stroke	Number of cycles before battery drained
650mm up, 650mm down per cycle	38
325mm up, 325mm down per cycle	76
217mm up, 217mm down per cycle	114

*Operate with free standing desk with TL4/TC15P under 120kg load

Warranty

1. 2 years warranty for the charging cradle
2. 1 year warranty for the battery pack

Drawing

Standard dimension (mm)

